



Description

Aluminum alloy guardrail to be mounted on the outside of the parapet wall.
 Comes complete with stainless steel brackets and fasteners, plastic end caps, and optional toeboard.

Relevant regulations

ISO 14122 - 3

Technical data

| | |
|-------------------------------|--------------------------|
| Guardrail height | 1300 mm |
| Parapet minimum height | 0 mm |
| Max distance between uprights | 1500 mm |
| Uprights angle | NA |
| Uprights measurements | 80x30 mm |
| Handrail pipe diameter | Ø40mm |
| Guardrail material | Aluminum alloy 6063 T6 |
| Brackets material | Stainless steel AISI 304 |
| Fasteners material | Stainless steel AISI 304 |
| End caps material | PE-LD |

Mounting methods

| Type | Tensile strength |
|--|------------------|
| 12x110 threaded rod with chemical anchor | 1300 Kg |
| 12x110 concrete screw | 1300 Kg |
| 12x114 concrete dowel | 1300 Kg |

Additional features

Toeboard

Anodizing

Power coating

Access gate

Custom mounting brackets

Non-standard height & incline available on request

CREDA Enterprise Srl

Legal Office: Via Monte Rosa, 21 | 20149 Milano (MI)
 Operating Office: Via Pacinotti, 42 | 20090 Corsico (MI)
 02/47753091 | credaelevation.it | info@credae360.it